

## **Red Standard**

0-0-60

Chemical Composition					
Component	Symbol	Typical	Guarantee		
Potassium Oxide Equivalent	K <sub>2</sub> O	61.0 %	60% Minimum		
Potassium Chloride	KCl	96.6 %			
Sodium Chloride	NaCl	2.6 %			
Chloride	Cl-	47.5 %			
Moisture	H₂O	0.04 %			

Particle Size Distribution Cumulative %					
US Mesh	Opening (mm)	Typical Range	Typical		
12	1.700	0 - 15	7		
16	1.180	15 - 55	35		
20	0.850	30 - 85	56		
40	0.425	60 - 100	88		
70	0.212	85 - 100	99		
	12 16 20	US Mesh Opening (mm)   12 1.700   16 1.180   20 0.850   40 0.425	US Mesh Opening (mm) Typical Range   12 1.700 0 - 15   16 1.180 15 - 55   20 0.850 30 - 85   40 0.425 60 - 100		

Physical Properties			
Parameter	Typical		
Bulk Density (Loose)			
- lb/ft³	76		
- kg/m³	1218		
Angle of Repose	35 Degrees		

Sizing Characteristics			
Typical			
95			

## Please refer to the Safety Data Sheet (SDS #: MOS100052) for additional information (www.mosaicco.com)

The information contained in this data sheet is a representation of the average properties of product analyses as tested on composite samples and typical analyses should not be considered a guaranteed specification. Individual shipment and grab sample analyses may fall outside of the above typical values Additional handling, transportation, or improper/extended storage may affect product analyses. Mosaic disclaims any responsibility or liability for any loss or damage that may occur from any reliance on, or other use of, the above information with respect to the product.